# Left-hand drive vehicles

### Vehicle Standards Fact Sheet



MR629 06/17

This fact sheet applies as of 1 July 2017 to lefthand drive vehicles with a gross vehicle mass less than or equal to 4.5 tonnes. It provides guidance information on the eligibility criteria for granting left-hand drive exemptions for vehicle registration.

It is the vehicle owner's responsibility to read this document carefully and conform to the requirements in this fact sheet.

Under South Australian legislation, a motor vehicle must be right-hand drive. A right-hand drive vehicle is defined as having at least one steering control to the right of the vehicle's longitudinal centre line. However, it is recognised that the historic character of older vehicles may be compromised by converting it to right-hand drive.

The Minister for Transport and Infrastructure has approved the issue of left-hand drive exemptions for left-hand drive vehicles that are 30 years of age or older as from 1 January of the year of vehicle manufacture. The exemption must be obtained as a pre-requisite to these vehicles being granted registration in South Australia.

#### Eligibility for left-hand drive exemption

Two types of left-hand drive exemptions are available in South Australia:

- Single trip left-hand drive exemption.
- Unrestricted left-hand drive exemption.

#### Single trip left-hand drive exemption

This exemption allows a single nominated trip of a left-hand drive vehicle under given conditions.

The use of this exemption is limited to trips related to initial delivery, government inspection and conversion to right hand drive. The exemption **cannot** be used for road testing or other purposes.

The driver must carry the exemption in the vehicle at all times and it must be used in conjunction with:

- single day registration permit; or
- trade plate, where applicable.

The exemption application (MR851) can be downloaded at <a href="http://www.sa.gov.au">http://www.sa.gov.au</a> and submitted to Vehicle Standards via fax on 08 8348 9533 or email at <a href="http://www.sa.gov.au">dpti.vehiclestandards@sa.gov.au</a>.

If you have any inquiries please contact Vehicle Standards on 1300 882 248.

#### **Unrestricted left-hand drive exemption**

This exemption allows registration and operation of a lefthand drive vehicle that is 30 years of age or older as from 1 January of the year of vehicle manufacture.

The driver must carry the exemption in the vehicle at all times and it must be used in conjunction with:

- Full or historic registration;
- Single day registration permit; or
- Trade plate, where applicable.

For the exemption to be issued, the vehicle must meet the requirements in this fact sheet and pass both identification and roadworthy inspections undertaken in South Australia.

#### Inspection

Please note an identification inspection **must** be undertaken and completed **prior to** a roadworthy inspection being started.

Further information Call 1300 882 248 Visit sa.gov.au

Email dpti.vehiclestandards@sa.gov.au



#### Identification inspection

Identification inspections do not require a booking.

Identification inspections are undertaken at any of the following locations:

- 7 Naweena Road, Regency Park
  - o 8:00 AM to 4:30 PM
  - Monday to Friday (close on public holidays)
- Unit 2/7 Ellemsea Circuit, Lonsdale
  - o 9:00 AM to 12:00 PM and 1:00 PM and 3:00 PM
  - Wednesday and Thursday (close on public holidays)

The information about identification stations can be found from Fact Sheet MR1561.

#### Roadworthy inspection

Roadworthy inspections require a booking by telephoning Service SA on 13 10 84.

Roadworthy inspections are undertaken at:

• 13 Kateena Street, Regency Park

Country inspections can be arranged in regional areas.

A copy of the Import Approval documents issued by the Department of Infrastructure and Regional Development (DIRD) must be supplied and retained by the inspecting officer at the time of inspection, in addition to any requested engineering certification.

#### Vehicle modifications

Left-hand drive vehicles may be modified from their original design and exemptions from legislative requirements for the modification/s may be required. This is for cases where the modifications make a vehicle non-compliant with vehicle standards legislation.

Please refer to the requirements and processes detailed in Fact Sheet <u>MR1457</u> on vehicle modifications for guidance and contact Vehicle Standards, as required.

#### **General requirements**

The vehicle must comply with the following requirements, regardless of the year of manufacture, in addition to the requirements in the South Australian *Road Traffic Act 1961* and its Regulations.

#### **Mirrors**

 A left-hand drive vehicle must be fitted with both left and right-hand side external mirrors.

#### Lighting

- Headlamps must be fitted with a dipping device to deflect the light projected from the headlamps downwards or downwards and to the left.
- Front parking lights must be white or yellow and rear parking lights must be red.
- A red rear facing reflector must be mounted either side at the rear of the vehicle at right angles to the road surface.
- Vehicles manufactured after August 1966 but prior 1 July 1973 must be fitted with red or yellow rear indicator lamps and white or yellow front indicator lamps.
- Vehicles manufactured on or after July 1973 must be fitted with yellow front and rear indicator lamps.
- For vehicles manufactured after December 1969, the parking lights must also be on when the headlamps are switched on.

#### Seat belt and seat belt anchorage

- All seat belts must be fitted in accordance with either the vehicle or seatbelt manufacturer's requirements.
- If lap/ sash seat belts are required to be fitted and the vehicle has insufficient original anchorage points a report from a Light Vehicle Engineering Signatory (MR426) may be required on the additional anchorage points.

## Requirements specific to the year of manufacture

The vehicle will also need to comply with certain requirements specific to the year of manufacture, in addition to **General requirements**.

#### Vehicle built before 1 January 1967

- There are no requirements for seat belts to be fitted to the vehicle.
- If seat belts are fitted they must comply with at least Australian Standard (AS) E35-1935 or AS 2596-83 and be fitted correctly.

Vehicle built between 1 January 1967 and 31 December 1968

- Seat belts for front outboard positions complying with at least Australian Standard (AS) E35 – 1935 or AS 2596 – 83.
- Lap or lap/sash seat belts are acceptable and must be fitted correctly.

Vehicle built between 1 January 1969 and 31 December 1970

- Seat belts for all front seating positions complying with at least ADR 4.
- Lap/sash seat belts for outboard positions and lap seat belts for the inboard position.
- All seat belts to have non-partial engagement type buckles.

Call 1300 882 248 Visit sa.gov.au

Email dpti.vehiclestandards@sa.gov.au



### Vehicle built between 1 January 1971 and 31 December 1971

- Seat belts for all seating positions complying with at least ADR 4
- Lap/sash seat belts for outboard positions and lap seat belts for inboard positions.
- All seat belts to have non-partial engagement type buckles.

## Vehicle built between 1 January 1972 and 31 December 1974

- Seat belts for all seating positions complying with at least ADR 4 & 4A for vehicles built after 1<sup>st</sup> January 1974.
- Lap/sash seat belts for outboard positions and lap seat belts for inboard positions.
- All seat belts to have non-partial engagement type buckles.
- Head restraints for all front outboard seating positions complying with at least ADR 22.

### Vehicle built between 1 January 1975 and 31 December 1975

- Seat belts for all seating positions complying with at least ADR 4B.
- Emergency Locking Retractor (ELR) lap/sash seat belts for front outboard positions, lap/sash seat belts for all rear outboard positions and lap seat belts for inboard positions.
- ELR seat belts may be single or dual locking. All seat belts to have non-partial engagement type buckles.
- Head restraints for all front outboard seating positions complying with at least ADR 22A.

## Vehicle built between 1 January 1976 and 31 December 1976.

- Seat belts for all seating positions complying with at least ADR 4C.
- ELR lap/sash seat belts for front outboard positions, lap/sash seat belts for all rear outboard positions and lap seat belts for inboard positions.
- ELR seat belts may be single or dual locking. All seatbelts to have non-partial engagement type buckles.
- Head restraints for all front outboard seating positions complying with at least ADR 22A.
- Child restraint anchorages must be fitted in accordance with at least ADR 34 for at least three seating positions.

### Vehicle built between 1 January 1977 and 31 December 1983

- Seat belts for all seating positions complying with at least ADR 4C.
- ELR lap/sash seat belts for front outboard positions, lap/sash seat belts for all rear outboard positions and lap seat belts for inboard positions.

- ELR seat belts must be dual locking and all seat belts to have non-partial engagement type buckles.
- Head restraints for all front outboard seating positions complying with at least ADR 22A.
- Child restraint anchorages must be fitted in accordance with at least ADR 34 for at least three seating positions.
- An engineering report to be supplied from a Light Vehicle Engineering Signatory (MR426) that verifies that the vehicle complies with the requirements of ADR 29: Side Door Strength.

### Vehicle built between 1 January 1984 and 31 December 1985

- Seat belts for all seating positions complying with at least ADR 4D.
- ELR lap/sash seat belts for both front and rear outboard positions and lap seat belts for inboard positions.
- ELR seat belts must be dual locking and all seat belts to have non-partial engagement type buckles.
- Head restraints for all front outboard seating positions complying with at least ADR 22A.
- Child restraint anchorages must be fitted in accordance with ADR 34 for at least three seating positions.
- An engineering report to be supplied from a Light Vehicle Engineering Signatory (MR426) that verifies that the vehicle complies with the requirements of ADR 29-Side Door Strength.

#### Vehicle built between 1 January 1986 and 30 June 1988.

- Seat belts for all seating positions complying with at least ADR 4D.
- ELR lap/sash seat belts for both front and rear outboard positions and lap seat belts for in board positions.
- ELR seat belts must be dual locking and all seat belts to have non-partial engagement type buckles.
- Head restraints for all front outboard seating positions complying with at least ADR 22A.
- Child restraint anchorages must be fitted in accordance with ADR 34 for at least three seating positions.
- An engineering report to be supplied from a Light Vehicle Engineering Signatory (MR426) that verifies that the vehicle complies with the requirements of ADR 29/.. Side Door Strength.
- Petrol powered vehicles must be fitted with an effective catalytic converter in the vehicle exhaust system.

**Disclaimer:** The information and data on this fact sheet is subject to change without notice. The Government of South Australia may revise this information at any time by updating this fact sheet.

